

Item Number PRX+0900 Series Contact Form C Switch Configuration SPST Rev. E

### Form C Threaded Proximity Sensor


Features	Advantages
<ul style="list-style-type: none"> <li>Hermetically sealed Rhodium contacts</li> <li>Position adjustable</li> <li>Materials are Lead free and RoHS compliant</li> </ul>	<ul style="list-style-type: none"> <li>UL94 flame rated black Valox housing</li> <li>Custom sensitivity and configurations available</li> <li>Not ESD sensitive</li> </ul>

### Electrical Specifications

Power		Watts - maximum	3
Voltage	Switching	VDC - maximum	120
	Breakdown	VDC - minimum	400
Current	Switching	Amp - maximum	0.25
	Carry	Amp - maximum	2.6
Resistance	Initial Contact Resistance	Ohm - maximum	0.25
	Insulation Resistance	Ohm - minimum	1 E9
Capacitance	Contact	pF - typical	1.7
Temperature	Operating	°C - maximum	+105
	Storage	°C	-40 to +140

### Physical/Operational Specifications

Housing Volume	Excluding Connection	CC - nominal	1.90
External Connection	24AWG	UL 1007/1569	PVC
Must Operate	Distance (d)	Inches	0.200
Must Release	Distance (d)	Inches	0.750
Operate Time	Including Bounce	mSeconds - maximum	1.00
Release Time		mSeconds - maximum	0.80



#### Notes:

- Specifications are not constant across entire magnetic range.
- Customer must exercise care in handling and mounting to prevent damage to internal components and subsequent changes to sensor performance.
- For information about performance, mounting options, custom configurations (e.g. wire length or color, connectors, operational variation) or packaging contact our Sales Department.
- Information contained hereon is for informational purposes only and should not be deemed as accurate for a specific application. Consult factory for specific application information and/or latest revision.